### TECH SPECIFICATIONS

#### Camera

- 120° FOV
- Sony High-Sensitivity Camera Sensor
- f/1.8 Aperture
- UHD 2160p (4K) capture resolution
- Auto Framing and Speaker Tracking
- 5x digital zoom / EPTZ
- Smart HDR
- 2 Camera presets
- Camera indicator

### Audio

- Support full-duplex conversations, acoustic echo cancellation and background noise suppression
- Mute / Unmute controls
- Stereo microphone:
  - 6-element beamforming microphone array
  - 19.7ft / 6m pickup range
  - 120 Hz-16 kHz frequency response
- Single speaker:
  - 100Hz-20KHz Frequency response
  - Output = 90 dB @ 0.5m

# **Application Requirements**

- Supported operating systems
  - Windows 7、8.1、10、11
  - MacOS<sup>®</sup> 10.15 or Higher
  - − Chrome OS™
  - Android<sup>™</sup> 6.0 or Higher
- Supports standard audio and video device drivers
  - UAC 1.0 Audio
  - UVC 1.1/1.5 Video
  - HID 1.11

### Interfaces

- 1x USB2.0 Type-C port
- 1x USB3.0 Type-A port
- Power connector
- Bluetooth control key
- Kensington security lock
- Bluetooth 4.2

## **Application Compatibility**

- Compatible with any application that supports standard USB audio and video drivers, including but not limited to:
- Skype for Business
- Microsoft Teams
- Zoom
- GoToMeeting
- BlueJeans
- Welink
- Google Meet
- Amazon Chime
- Cisco Webex
- Slack
- Compatible with Clickshare CX-20/ CX-30/CX-50

# Power Requirements

• 5VDC/2A@100~240VAC, 50/60Hz

# Package Contents

- OneView N110
- Remote control with 2 AAA batteries
- Power adapter
- 5m USB2.0 cable (Type–C to Type–A)
- Wall mount kit
- Setup sheet

## Size and weight

- Size (H x W x D):
  98 x 505 x 72 (MM)
  3.9 x 19.9 x 2.8 (Inches)
- Weight:3.7 lbs 60 oz (1.7 kg)

### Environmental

- Working temperature:
   32~104°F (0–40°C)
- Relative humidity:
  5~95%, noncondensing
- Storage temperature:
  -13~160°F (-25~70°C)

## **Warranty Information**

 2-year limited hardware warranty

### Certifications



(





ISO 9001



For more information on OneView N110 visit <a href="www.nexvoo.com">www.nexvoo.com</a>

